



RED LINE SYNTHETIC OIL CORP.

6100 Egret Court, Benicia, CA 94510 USA Tel: 707-745-6100 FAX: 707-745-3214
 www.redlineoil.com email: redline@redlineoil.com

Synthetic Gear Lubricants

Red Line Gear Oils are designed to provide excellent low-temperature characteristics and improved gear protection at higher temperatures. Red Line Gear Oils will reduce differential temperatures 10-70°F. Efficiency improvements between 1-5% are typical. The synthetic base stocks used have tremendous thermal stability and provide the best film strength available. The unique combination of base stocks and additives allow Red Line gear oils to carry higher loads compared to petroleum lubricants. The stability of these products allow them to be used for extended periods. Red Line 75W90 Gear Oil provides excellent protection in nearly all differentials, conventional and limited slip, in both racing and street use. 75W90NS and 75W140NS can be used in certain limited-slip units in racing to lock-up the differential. 80W140 should be used in commercial hauling, problem limited-slip units, racing applications which see tremendous torque at low speeds, and where noise deadening is desired. 75W85 can be used to obtain maximum power transfer in racing differentials which do not see extremely high temperatures and improved efficiency in street differentials. If “chattering” occurs with any of these lubricants, Red Line Limited Slip Friction Modifier can be used to eliminate the stick/slip action and reduce the noise. This additive should not be necessary in the 75W90, 75W110, 75W140 or the 80W140 Gear Oils, since they already contain this additive, but in some units more is required. Too much friction modifier can reduce the lockup in limited slip units, so it should only be used if needed.

Typical Properties

	75W85	75W90	75W110	75W90NS	80W140	75W140NS	75W140
API Service Class:	GL 5	GL 5	GL 5+	GL 5+	GL 5+	GL 5+	GL 5+
Viscosity Grade: SAE	75W85	75W90	75W110	75W90	80W140	75W140	75W140
Vis @ 100°C, cSt	11.5	16.1	20.9	15.6	26	26.9	27.8
Vis @ 40°C, cSt	68	112	131	95	227	179	192
Viscosity Index	163	154	184	176	146	188	183
Brookfield Viscosity, Poise	300 @ -40°C	1100 @ -40°C	830 @ -40°C	400 @ -40°C	500 @ -26°C	1200 @ -40°C	1300 @ -40°C
Pour Point, °C	-45	-45	-42	-45	-40	-45	-45
Pour Point, °F	-49	-49	-44	-49	-40	-49	-49